

**Série 6, Micro-ondes intégrable, 60 x 38 cm, Inox
BEL524MS0**



1 x grille, 1 x Plateau tournant

HEZ86D000 ACCESSOIRE VAPEUR POUR MICRO-ONDES

Micro-ondes encastrable pour une niche de 38 cm : décongeler, chauffer et préparer à la perfection vos aliments.

- **Boutons push-pull** : facilite le nettoyage.

Fonction additionnelle: Fonction Grill
Type de commandes: Electronique
Dimensions appareil H x L x P:382x594x317 mm
Dimensions de la cavité: 201 x 308 x 282 mm
Longueur du cordon électrique: 130.0 cm
Poids net: 17.2 kg
Poids brut: 19.5 kg
Code EAN: 4242005038879
Puissance maximum du micro-ondes: 800 W
Puissance de raccordement: 1270 W
Intensité: 10 A
Tension: 220-230 V
Fréquence: 50 Hz
Type de prise:Fiche cont.terre/Gard.fil ter.
Accessoires inclus: 1 x grille, 1 x Plateau tournant



**Série 6, Micro-ondes intégrable, 60 x
38 cm, Inox
BEL524MS0**

**Micro-ondes encastrable pour une niche
de 38 cm : décongeler, chauffer et
préparer à la perfection vos aliments.**

Design :

- Display LED
- Boutons escamotables, Boutons push-pull, commandes par touchControl
- Commande par touches sensibles

Caractéristiques principales :

- Volume 20 l
- 5 Puissances micro-ondes : 90 W, 180 W, 360 W, 600 W, 800 W
- 8 programmes automatiques
- 4 décongélation et 3 micro- ondes, 1 programme en combiné
- Fonction mémoire (1 position)
- Gril de 1 kW
- Puissance du gril et du Micro ondes 90 W, 180 W, 360 W combinable
- Les modes de cuisson micro-ondes et grill peuvent être utilisés séparément ou combinés

Confort/Sécurité :

- Plateau tournant en verre : 25.5 cm
- Horloge électronique
- Eclairage LED
- Cavité Acier inox
- Charnières à gauche
- Ouverture de la porte électronique

Données techniques :

- Câble de raccordement : 130 cm
- Puissance totale de raccordement : 1.27 kW
- Tension nominale : 220 - 230 V

© 2015 Pearson Education, Inc. or its affiliate(s). All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage or retrieval system, without prior written permission from the publisher.

The image contains two technical drawings of a door frame. The left drawing shows a side view of a door in its closed position, with a dimension line indicating a minimum clearance of 3 units between the door edge and the frame. The right drawing shows a top-down view of the door frame assembly, with a circular callout providing a magnified detail of the corner joint. This detail shows the door, frame, and floor, with a dimension line indicating a minimum clearance of 3 units between the door and the frame at the corner.

Mesures en mm

Technical drawings of two rectangular boxes, (A) and (B), showing their dimensions.

Box (A):

- Length: 594
- Width: 297
- Height: 382
- Side panel height: 346
- Bottom flange thickness: 19

Box (B):

- Length: 600
- Width: 560+8
- Height: 362+3
- Side panel height: 16
- Minimum depth: ≥ 300

Technical drawing of a 20 litre container. The drawing shows a top-down view of a rectangular container with a smaller rectangular opening in the center. The overall width is dimensioned as 550. The overall height is dimensioned as 380-382. The height of the central opening is dimensioned as 2-0. The text "20 litre" is written inside the central opening.

3 /

